# ZMD-DH-SEN6 How to connect the SCN4, SCN8, and SEN6 to the General CMS software

This is a tutorial on how to connect DVRs with the SKU numbers SCN4, SCN8 and SEN6 to the General CMS software that came with the DVR units. If you have misplaced the disc, click <u>here</u> to download the software.

1. When you first open the software, there will be a warning that there is no device connected.



Click **OK** and then select the option for **System** as shown below.

СМS		- = ×
Device	Monitor	Time
		14:17:26 2014-04-29
		PTZ
		<ul> <li>Zoom</li> <li>Focus</li> <li>Iris</li> <li>Pan</li> </ul>
		Preset 01 V () + - Tour 01 V   = ##
1	E III III III 25 36 64 X 4/2	S PTZ
4	Type Date Device User Describe	Color
		System
		PlayBack
		I Advance
୍ର୍ଟ		S LogOut

2. Select the option for **Device Manager**.

СМS		- = ×
Device	Monitor	Time
		14:16:12 2014-04-29
		System
		۲
		Device Manager
		Local Config
		Remote Config
		Account
		Local Log
		🍯 РТД
		Color
	Type Date Device User Describe	
		Magn
		Advance
्रट		25 LogOut

3. This should open up a new window. Select Add Area.



4. For the **Zone** enter a description of the location of the DVR, for example Home or Work. Then click **OK**. This is to help organize your DVRs if you have multiple DVRs in different locations.

Device Manager							×
<b>1</b>	A 1	0	Î	<u></u>			
ADD AREA	ADD DEVICE	MODIFY	DELETE	Devices impor	tDevices export	Connection Test	
	Zone Zone Up Zone	Test OK		Cancel	×		
			ОК	]			

5. The zone you created will apear in the Zone List. Select the zone that you created, and then the option to **Add Device** will appear.



6. Before adding the new device, the DVR should already be setup for local or remote access. You will also need all the IP addresses, port numbers, and login information already setup on your DVR.

- Name: this can be whatever you like it to be
- IP Address:
  - If you are on the same local network, you will use your local IP address that should be listed in the Network section on the DVR (Usually 192.168.x.x or 10.0.x.x)
  - If you are away from the location, you will use your External or Public IP address.
- Port: By default it should be 34567, unless it has been changed on DVR's network settings
- Username/Password: This will be the username and password you use to access the DVR.
  - It may be the administrator username and password for full privileges.
  - It can aslo be a custom username and password that was created for specific users with limited access.

(c) 2025 Jeremy Schultz <itmanager@eptco.com> | 2025-07-16 17:39

 $\label{eq:url:https://kb.zmodo.com/index.php?action=artikel\&cat=7\&id=314\&artlang=en$ 

Device Manage	r X
Ę	Edit
ADD AF	NO. IP Address Port MAC Vendor on Test
Zone E	IP Search Add Device   EditDevice   Device Name   Test   LoginType IP Address   Domain ARSP   Cloud   IP Address   · · ·   Port 34567   User Name admin   Password   Zone   Test   Vendor   H264DVR
	OK

Once you have all that information filled out. Click **OK** and you should see your Device Name that you created listed underneath the Zone. Click **OK** again to go back to main screen.

7. You can now d**ouble-click** on the Device Name listed under the Device List. You should see on the bottom that it says **Connect Successful**, and your camera channels will appear under the DVR Device Name.

СМS						- = ×
Device				Monitor		Time
<ul> <li>Test</li> <li></li></ul>						14:22:51 2014-04-29
SC CANDY						PTZ
	,					Zoom     Zoom     Focus     Iris
						Pan • Preset 01 ▼ ○ + − Tour 01 ▼ ▶ ■ ₩
				25 36	64 🔀 🎼 📉	
1	Туре	Date	Device	User	Describe	Color
	Video	2014-04-29 14:22:18	Test	admin	Connect successful	System
	System Oper Video	2014-04-29 14:22:16 2014-04-29 14:21:52	Test Test	admin admin	Disconnect Connect successful	
	VIGEO	2017072917.21.32	reat	Gumm	connect succession	PlayBack
						Advance
୍ର୍ଟ						🥂 LogOut

8. To connect to the cameras, right-click on the Device Name and select the option for **Connect all Video**.

- Choose the **Main Stream** if you are local or want higher quality video, but this may take longer to load.
- The **Extra Stream** will give you a smoother image with a lower quality image.

You can also open each channel individually by first selecting a window with the green outline. Then double-click on one of the channels, for example CAM01, and the channel will appear in that window. Repeat the process for the other channels.

Unique solution ID: #1314 Author: Ed Lamont Last update: 2015-03-20 17:02