ZMD-DT-SFN6 How to set up ESEE mobile app

To set up the ESEE mobile app for your ZMD-DT-SFN6 DVR system, first install the app



You can program the app using the ESEE ID (found on the DVR's network setup page) or by it's IP address and port, just tap the option you would like to use.

ESee ID Address				
Address:				
Port: 88				
User ID: admin				
Password:				
Max Channel: 1 4 8 16 32				
Login				

Page 1 / 2 (c) 2025 Jeremy Schultz <itmanager@eptco.com> | 2025-06-30 18:16 URL: https://kb.zmodo.com/index.php?action=artikel&cat=171&id=347&artlang=en

ZMD-DT-SFN6

We recommend programming the system using the network ID. This is found at the top right on the network setup page in the DVR's network settings menu.

- Carlor				
Network setup				
DHCP IP address Gateway Web port This IP can be us 3G Status:	192.168. 11.160 192.168. 11. 1 90 ed. 3G Module Not Found	C ESee Subnet mask MAC address Preferred DNS PPPoE Status:	207570645 255.255.255. 0 0005-FR3E-7562 192.168.11. 1 Not connect	
PPPoE	DDNS 3G	EFFOR IF:	Cancel	

Unique solution ID: #1347 Author: Jamie Alksnis Last update: 2015-03-23 16:36