

ZMD-DT-SFN6

How to set up ESEE mobile app

To set up the ESEE mobile app for your ZMD-DT-SFN6 DVR system, first install the app



You can program the app using the ESEE ID (found on the DVR's network setup page) or by it's IP address and port, just tap the option you would like to use.

The image is a screenshot of the ESEENET mobile app's login screen. At the top, there is the ESEENET logo. Below it, there are two tabs: 'ESee ID' and 'Address'. The 'Address' tab is selected. The form contains the following fields: 'Address:' with an empty text input; 'Port:' with a text input containing '88'; 'User ID:' with a text input containing 'admin'; 'Password:' with a text input containing six dots; and 'Max Channel:' with a row of five buttons labeled '1', '4', '8', '16', and '32', where the '16' button is highlighted in blue. At the bottom of the form is a blue 'Login' button.

ZMD-DT-SFN6

We recommend programming the system using the network ID. This is found at the top right on the network setup page in the DVR's network settings menu.

Network setup

DHCP

ESee 207570645

IP address 192.168.11.160

Subnet mask 255.255.255.0

Gateway 192.168.11.1

MAC address 0005-FE3E-7562

Web port 90

Preferred DNS 192.168.11.1

This IP can be used.

3G Status: 3G Module Not Found

PPPoE Status: Not connect

3G IP: --

PPPoE IP: --

PPPoE DDNS 3G E-Mail

Ok Cancel

Unique solution ID: #1347
Author: Jamie Alksnis
Last update: 2015-03-23 16:36